



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.10.2022

Revision: 25.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** OPN-Foam Cut Spray
- **Articelnumber:** 60615
- **UFI:** 92VD-M5RY-300E-XQA7
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Metal working auxiliary
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
OPN-CHEMIE GmbH
In der Au 14
57290 Neunkirchen
www.opn-chemie.de
- **Further information obtainable from:**
Barbara Angelika Gros-Petri
baerbel.petri@opn-chemie.de
- **1.4 Emergency telephone number:** Vergiftungs-Informations-Zentrale Freiburg +49(0) 761 / 1 92 40

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
Eye Irrit. 2 H319 Causes serious eye irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
- **Precautionary statements**
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P271 Use only outdoors or in a well-ventilated area.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P501 Dispose of contents / container in accordance with national regulations of the disposal.

- **Additional labelling requirements:**
Buildup of explosive mixtures possible without sufficient ventilation.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

GB

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.10.2022

Revision: 25.03.2021

Trade name: **OPN-Foam Cut Spray**

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description:

Mixture of substances listed below with nonhazardous compounds or compounds with no duty to declare.

Dangerous components:

CAS: 57-55-6 EINECS: 200-338-0 Reg.nr.: 01-2119456809-23	Propylene glycol substance with a Community workplace exposure limit	25-50%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	Isobutane (< 0,1 % 1,3-butadiene) ⚠ Flam. Gas 1A, H220; Press. Gas (Liq.), H280	2.5-10%
CAS: 57635-48-0	Alkyl polyglycoether carboxylic acid ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315	≥3-<10%
CAS: 107-41-5 EINECS: 203-489-0	2-methylpentane-2,4-diol ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	≤2.5%
CAS: 110-97-4 EINECS: 203-820-9	1,1'-iminodipropan-2-ol ⚠ Eye Irrit. 2, H319	≤2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Induce vomiting, if person is conscious. Seek medical help.

Show this MSDS

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture Risk of bursting in case of fire heat

5.3 Advice for firefighters

Protective equipment: Wear fully protective suit.

Additional information Cool endangered receptacles with water spray.

GB

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.10.2022

Revision: 25.03.2021

Trade name: **OPN-Foam Cut Spray**

(Contd. of page 2)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Particular danger of slipping on leaked/spilled product.
Ensure adequate ventilation
Avoid contact with skin / eyes and inhalation.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections** Keep off any handling equipment with engines (source of ignition)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Avoid inhalation and contact with the skin and the eyes.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **Recommended storage temperature:** 15 - 35°C, max. 50°C
- **Storage class:** German storage class: 2B (Aerosols)
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

57-55-6 Propylene glycol

WEL (Great Britain)	Long-term value: 474* 10** mg/m ³ , 150* ppm *total vapour and particulates **particulates
---------------------	--

115-10-6 dimethyl ether

WEL (Great Britain)	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
IOELV (EU)	Long-term value: 1920 mg/m ³ , 1000 ppm

107-41-5 2-methylpentane-2,4-diol

WEL (Great Britain)	Short-term value: 123 mg/m ³ , 25 ppm Long-term value: 123 mg/m ³ , 25 ppm
---------------------	---

(Contd. on page 4)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.10.2022

Revision: 25.03.2021

Trade name: OPN-Foam Cut Spray

(Contd. of page 3)

· DNELs		
57-55-6 Propylene glycol		
Oral	DNEL Endverbraucher/ Consumers / Consommateur	85 mg/kg BW/ day (.) chronische Exposition, Systemische Wirkungen/ chronic exposition, systemic effects/ exposition chronique, effets systématique
Dermal	DNEL - Endverbraucher/ Consumers / Consommateur	213 mg/kg BW /day (.) chronische Exposition, Systemische Wirkungen/ chronic exposition, systemic effects/ exposition chronique, effets systématique
Inhalative	DNEL Endverbraucher/ Consumers / Consommateur	50 mg /m3 (.) chronische Exposition, Systemische Wirkungen/ chronic exposition, systemic effects/ exposition chronique, effets systématique
	DNEL Arbeiter / Workers/ Travailleur	168 mg /m3 (.) chronische Exposition, Systemische Wirkungen/ chronic exposition, systemic effects/ exposition chronique, effets systématique

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not necessary if room is well-ventilated.

· **Protection of hands:**

· **Material of gloves**



If contamination is possible, use gloves made of nitrile according EN 374

· **Penetration time of glove material** > 480 min / 0,4 mm thickness

· **Eye protection:** Safety glasses

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Aerosol
Colour:	Yellowish
Odour:	Characteristic

· **pH-value at 20 °C:** 7 - 8

· **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: -24 °C
value concerns to propellant

· **Flash point:** ca. -87 °C
concerns to propellant

· **Ignition temperature:** 235 °C

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.10.2022

Revision: 25.03.2021

Trade name: **OPN-Foam Cut Spray**

(Contd. of page 4)

· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Risk of bursting at temperatures > 50°C. Damage of the container may lead to the formation of explosive mixtures of gas/vapors with air.
· Explosion limits:	
Lower:	2.6 Vol %
Upper:	18.6 Vol %
Pressure (20°C)	3.5 - 5.0 bar
· Density at 20 °C:	ca. 0.935 g/cm ³
· Solubility in / Miscibility with water:	Fully miscible.
· Solvent content:	
VOC (EC)	47.30 % = 443 g/l
· 9.2 Other information	
Additional information	Vapors are heavier than air.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** Risk of bursting at temperatures >50°C.
- **10.3 Possibility of hazardous reactions**
By use or incidental release the formation of explosive vapor/air mixtures is possible.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Oxidizing agents.
- **10.6 Hazardous decomposition products:** In case of fire the formation of toxic gases is possible.
- **Additional information:** Stable for a storage time of min. 24 months

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

57-55-6 Propylene glycol

Oral	LD50	2,000 mg/kg (rat)
Dermal	LD50	20,800 mg/kg (rabbit)

115-10-6 dimethyl ether

Inhalative	LC50/4 h	308 mg/l (rat)
------------	----------	----------------

75-28-5 Isobutane (< 0,1 % 1,3-butadiene)

Inhalative	LC50/4 h	>20 mg/l (rat)
------------	----------	----------------

107-41-5 2-methylpentane-2,4-diol

Oral	LD50	3,700 mg/kg (rat)
Dermal	LD50	8,560 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** low irritant - no duty to declare
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.10.2022

Revision: 25.03.2021

Trade name: **OPN-Foam Cut Spray**

(Contd. of page 5)

- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

57-55-6 Propylene glycol

EC 50 / 48h	>100 mg / l (daphnia)
LC 50 / 96 h	>100 mg / l (Regenbogenforelle / Rainbow trout)

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

Ecotoxicological effects:

- **Remark:** Harmful to fish

Additional ecological information:

General notes:

Harmful to aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

empty cans: material recycling

filled cans: remove in accordance with local regulations

European waste catalogue

16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
16 05 00	gases in pressure containers and discarded chemicals
16 05 04*	gases in pressure containers (including halons) containing dangerous substances

Uncleaned packaging:

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA

UN1950

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.10.2022

Revision: 25.03.2021

Trade name: **OPN-Foam Cut Spray**

(Contd. of page 6)

· **14.2 UN proper shipping name**
 · **ADR** 1950 AEROSOLS
 · **IMDG** AEROSOLS
 · **IATA** AEROSOLS, flammable

· **14.3 Transport hazard class(es)**· **ADR**

· **Class** 2 5F Gases.
 · **Label** 2.1

· **IMDG, IATA**

· **Class** 2.1
 · **Label** 2.1

· **14.4 Packing group**· **ADR, IMDG, IATA** Void· **14.5 Environmental hazards:**· **Marine pollutant:** No· **14.6 Special precautions for user** Warning: Gases.· **Hazard identification number (Kemler code):** -· **EMS Number:** F-D,S-U· **Stowage Code**

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:

Category A. For AEROSOLS with a capacity above 1 litre:

Category B. For WASTE AEROSOLS: Category C, Clear

of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)** 1L· **Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

· **Transport category** 2· **Tunnel restriction code** D· **Remarks:**

Transportation as "LIMITED QUANTITIES" according 3.4 ADR is possible.

Sole marking: Sign for "Limited Quantities" (rhombus with two black edges)

Entry in the transportation document: Transportation according chapter 3.4 ADR

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.10.2022

Revision: 25.03.2021

Trade name: **OPN-Foam Cut Spray**

(Contd. of page 7)

·	Tunnel category "E" in case of a load of 8000 kg (rgross weight) or more.
· IMDG	1L
· Limited quantities (LQ)	Code: E0
· Excepted quantities (EQ)	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **National regulations:**

· **Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

Class	Share in %
Wasser	21.7
NK	31.4

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.10.2022

Revision: 25.03.2021

Trade name: OPN-Foam Cut Spray

(Contd. of page 8)

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Press. Gas (Liq.): Gases under pressure – Liquefied gas
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
· *** Data compared to the previous version altered.**

GB