



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

(This safety data sheet is for information only and does not
comply with the official language requirements of article 31 (5)
of REACH.)

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0
Replaces version of: 27.08.2020 (8)

Revision: 02.09.2024
First version: 01.05.2003

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **OPN-Special Coolant for the Welding Technology with frost protection to -10°C**

Article number **61096**

Unique formula identifier (UFI) **9D6F-25RW-E00F-4WM8**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Anti-freeze product

1.3 Details of the supplier of the safety data sheet

OPN-CHEMIE GmbH

In der Au 14

D-57290 Neunkirchen/Germany

Tel.: +49 (0) 2735/7725-0

Fax: +49 (0) 2735/7725-90

E-Mail: info@opn-chemie.de

Web: www.opn-chemie.de

Further information obtainable from:

Safety data sheets Mrs. Barbara Angelika Gros-Petri

Tel.: +49 (0) 2735/7725-20

E-Mail: baerbel.petri@opn-chemie.de

1.4 24 hours Emergency telephone number

Poison Information Center Freiburg +49(0)761/19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

| Classification | | | | |
|----------------|-----------------------------------|----------|---------------------------|------------------|
| Section | Hazard class | Category | Hazard class and category | Hazard statement |
| 2.6 | flammable liquid | 3 | Flam. Liq. 3 | H226 |
| 3.3 | serious eye damage/eye irritation | 2 | Eye Irrit. 2 | H319 |

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word warning

Pictograms

GHS02, GHS07



Hazard statements

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTRE/doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents / container in accordance with national regulations of the disposal.

Additional labelling requirements see section 15 of the safety data sheet

2.3 Other hazards

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0,1\%$.

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture).

3.2 Mixtures

Description of the mixture

| Hazardous ingredients | | | | |
|-----------------------|--|-----------|--|-----------------|
| Name of substance | Identifier | Wt% | Classification acc. to GHS | Notes |
| propan-2-ol | CAS No 67-63-0 EC No 200-661-7 Index No 603-117-00-0 REACH Reg. No 01-2119457588-25 | 10 – < 20 | Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336 | GHS-HC |
| ethylene glycol | CAS No 107-21-1 EC No 203-473-3 Index No 603-027-00-1 REACH Reg. No 01-2119456816-28- xxxx | 5 – < 10 | Acute Tox. 4 / H302 STOT RE 2 / H373 | GHS-HC IOELV |

Notes

GHS- Harmonised classification (the classification of the substance corresponds to the entry in the list according to HC: 1272/2008/EC, Annex VI)

IOELV: Substance with a community indicative occupational exposure limit value

| Name of substance | Specific Conc. Limits | M-Factors | ATE | Exposure route |
|-------------------|-----------------------|-----------|-----------|----------------|
| ethylene glycol | - | - | 500 mg/kg | oral |

Remarks

For full text of H-phrases: see SECTION 16

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Self-protection of the first aider.

Remove affected person from the danger area and lay down.

Do not leave affected person unattended.

Take off immediately all contaminated clothing.

In all cases of doubt, or when symptoms persist, seek medical advice.

Following inhalation

Provide fresh air.

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions.

Mouth to mouth resuscitation should be avoided. Use alternative methods, preferably with oxygen or compressed air driven apparatus.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Following ingestion

Rinse mouth. Do not induce vomiting.

Get medical advice/attention if you feel unwell.

Notes for the doctor

None.

4.2 Most important symptoms and effects, both acute and delayed

This information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

water spray, alcohol resistant foam, fire extinguishing powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

5.2 Special hazards arising from the substance or mixture

Combustible.

Hazardous decomposition products: Section 10.

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

Solvent vapours are heavier than air and may spread along floors.

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

carbon monoxide (CO), carbon dioxide (CO₂)

5.3 Advice for firefighters

Keep containers cool with water spray.

In case of fire and/or explosion do not breathe fumes.

Co-ordinate firefighting measures to the fire surroundings.

Do not allow firefighting water to enter drains or water courses.

Collect contaminated firefighting water separately.

Fight fire with normal precautions from a reasonable distance.

Special protective equipment for firefighters

Wear self-contained breathing apparatus

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

Ventilate affected area.

Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water.

Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to clean up a spill

Collect spillage.

Absorbent material (e.g. sand, diatomaceous earth, acid binder, universal binder, sawdust, etc.).

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal.

Ventilate affected area.

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

6.4 Reference to other sections

Hazardous combustion products: see section 5.

Personal protective equipment: see section 8.

Incompatible materials: see section 10.

Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes.

Do not breathe vapour/spray.

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation.

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Measures to protect the environment

Avoid release to the environment.

Advice on general occupational hygiene

Do not eat, drink and smoke in work areas.

Wash hands after use.

Preventive skin protection (barrier creams/ointments) is recommended.

Remove contaminated clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities

Explosive atmospheres

Keep container tightly closed and in a well-ventilated place.

Use local and general ventilation.

Keep cool.

Protect from sunlight.

Flammability hazards

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharge.

Ground/bond container and receiving equipment.

Protect from sunlight.

Incompatible substances or mixtures

Incompatible materials: see section 10.

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

Protect against external exposure, such as
heat

Consideration of other advice

Keep away from food, drink and animal feedingstuffs.

General rule

Keep out of reach of children.

Ventilation requirements

Provision of sufficient ventilation.

Specific designs for storage rooms or vessels

Keep container tightly closed and in a well-ventilated place.

Keep cool.

Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Occupational exposure limit values (Workplace Exposure Limits) | | | | | | | | | |
|---|----------------------|---------------|-------------------|------------------|--------------------|-------------------|---------------------|-----------------|---------------|
| Country | Name of agent | CAS No | Identifier | TWA [ppm] | TWA [mg/m³] | STEL [ppm] | STEL [mg/m³] | Notation | Source |
| DE | ethanediol | 107-21-1 | AGW | 10 | 26 | 20 | 52 | va, H, Y | TRGS 900 |
| DE | ethylene glycol | 107-21-1 | MAK | 10 | 26 | 20 | 52 | va, H | DFG |
| DE | 2-propanol | 67-63-0 | MAK | 200 | 500 | 400 | 1.000 | - | DFG |
| DE | propan-2-ol | 67-63-0 | AGW | 200 | 500 | 400 | 1.000 | Y | TRGS 900 |
| EU | ethylene glycol | 107-21-1 | IOELV | 20 | 52 | 40 | 104 | H | 2000/39/EC |

Notation

| | |
|------|--|
| H | absorbed through the skin |
| STEL | short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) |
| TWA | time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) |
| va | as vapours and aerosols |
| Y | a risk of developmental toxicity does not need to be expected if the occupational exposure limit value and the biological limit value (BGW) are adhered to |

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

| Biological limit values | | | | | | | |
|-------------------------|---------------|-----------|----------|------------|---------|-------------|----------|
| Country | Name of agent | Parameter | Notation | Identifier | Value | Material | Source |
| DE | 2-propanol | acetone | - | BAT | 25 mg/l | whole blood | DFG |
| DE | 2-propanol | acetone | - | BAT | 25 mg/l | urine | DFG |
| DE | propan-2-ol | acetone | - | BLV | 25 mg/l | whole blood | TRGS 903 |
| DE | propan-2-ol | acetone | - | BLV | 25 mg/l | urine | TRGS 903 |

Human health values

| Relevant DNELs of components | | | | | | |
|------------------------------|----------|-----------|-----------------------|------------------------------------|-------------------|----------------------------|
| Name of substance | CAS No | End-point | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
| propan-2-ol | 67-63-0 | DNEL | 500 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| propan-2-ol | 67-63-0 | DNEL | 888 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| ethylene glycol | 107-21-1 | DNEL | 35 mg/m ³ | human, inhalatory | worker (industry) | chronic - local effects |
| ethylene glycol | 107-21-1 | DNEL | 106 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |

8.2 Exposure controls

Appropriate engineering controls

Use local and general ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Use protective eyewear to guard against splash of liquids (EN 166).

Hand protection

| Protective gloves | | |
|-------------------------------------|--------------------|--|
| Material | Material thickness | Breakthrough times of the glove material |
| NBR: acrylonitrile-butadiene rubber | ≥ 0,4 mm | no information available |

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

Wear suitable gloves.

Chemical protection gloves are suitable, which are tested according to EN 374.

Check leak-tightness/impermeability prior to use.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

Protective clothing against liquid chemicals.

(EN 13832, EN 340, EN 14605).

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).

(EN 136, EN 140, EN 14387, EN 143, EN 149).

Environmental exposure controls

Use appropriate container to avoid environmental contamination.

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|---|--|
| Physical state | liquid |
| Colour | colourless |
| Odour | characteristic |
| Melting point/freezing point | not determined |
| Boiling point or initial boiling point and boiling range | ~80 °C |
| Flammability | flammable liquid in accordance with GHS criteria |
| Lower and upper explosion limit | not determined |
| Flash point | <55 °C |
| Auto-ignition temperature | not determined |
| Decomposition temperature | not relevant |
| pH (value) | not determined |
| Kinematic viscosity | not determined |
| Dynamic viscosity | not determined |
| Solubility(ies) | |
| Water solubility | miscible in any proportion |
| Partition coefficient n-octanol/water (log value) | not determined |

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

| | |
|--|---|
| Vapour pressure | not determined |
| Density and/or relative density | |
| Density | 0,9 – 1,1 g/cm ³ at 20 °C |
| Relative vapour density | information on this property is not available |

| | |
|---------------------------------|--------------------------|
| Particle characteristics | not relevant (liquid) |
|---------------------------------|--------------------------|

9.2 Other information

| | |
|---|------------------------------------|
| Information with regard to physical hazard classes | there is no additional information |
|---|------------------------------------|

| | |
|-------------------------------------|------------------------------------|
| Other safety characteristics | there is no additional information |
|-------------------------------------|------------------------------------|

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions.

If heated:

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharge.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

10.5 Incompatible materials

oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known.

Hazardous combustion products: see section 5.

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Classification procedure

If not otherwise specified the classification is based on:

Ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Test data are not available for the complete mixture.

| Acute toxicity of components | | | | | | | |
|------------------------------|----------|----------------|-----------|--------------|---------|--------------------|--------|
| Name of substance | CAS No | Exposure route | End-point | Value | Species | Method | Source |
| propan-2-ol | 67-63-0 | oral | LD50 | 5.840 mg/kg | rat | OECD Guideline 401 | ECHA |
| propan-2-ol | 67-63-0 | dermal | LD50 | 13.100 mg/kg | rabbit | OECD Guideline 402 | ECHA |
| ethylene glycol | 107-21-1 | dermal | LD50 | >3.500 mg/kg | mouse | - | ECHA |

Skin corrosion/irritation

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Respiratory sensitisation

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Germ cell mutagenicity

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Carcinogenicity

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

Reproductive toxicity

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

Specific target organ toxicity - single exposure

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Specific target organ toxicity - repeated exposure

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity (acute)

Based on available data, the classification criteria are not met.

Aquatic toxicity (acute) of components

| Name of sub-stance | CAS No | Endpoint | Expos-ure time | Value | Species | Method | Source |
|--------------------|----------|----------|----------------|--------------|---|--------------------------|--------|
| propan-2-ol | 67-63-0 | LC50 | 96 h | 9.640 mg/l | fathead min- now (Pimephales promelas) | OECD Guideline 203 | ECHA |
| propan-2-ol | 67-63-0 | LC50 | 24 h | >10.000 mg/l | daphnia magna | OECD Guideline 202 | ECHA |
| ethylene glycol | 107-21-1 | LC50 | 96 h | >72.860 mg/l | fathead min- now (Pimephales promelas) | EPA 600/4- 90/027 | ECHA |
| ethylene glycol | 107-21-1 | EC50 | 48 h | >100 mg/l | daphnia magna | OECD Guideline 202 | ECHA |

Aquatic toxicity (chronic)

Based on available data, the classification criteria are not met.

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

Aquatic toxicity (chronic) of components

| Name of sub- stance | CAS No | Endpoint | Expos- ure time | Value | Species | Method | Source |
|------------------------|----------|--------------------|-----------------------|-------------|---|--------------------|--------|
| propan-2-ol | 67-63-0 | NOELR | 28 d | >1.000 mg/l | fish | Qsar | ECHA |
| propan-2-ol | 67-63-0 | NOELR | 21 d | >1.000 mg/l | daphnia magna | Qsar | ECHA |
| ethylene glycol | 107-21-1 | LC50 | 28 d | >1.500 mg/l | tidewater silverside (Menidia peninsulae) | ASTM E-47.01 | ECHA |
| ethylene glycol | 107-21-1 | NOEC | 28 d | >40 mg/l | tidewater silverside (Menidia peninsulae) | ASTM E-47.01 | ECHA |
| ethylene glycol | 107-21-1 | NOEC | 72 h | >100 mg/l | algae (pseudokirchneriella subcapitata) | OECD Guideline 201 | ECHA |
| ethylene glycol | 107-21-1 | NOEC | 7 d | 8.590 mg/l | Ceriodaphnia dubia (water flea) | EPA 600/4-89/001 | ECHA |
| ethylene glycol | 107-21-1 | growth (Eb-Cx) 20% | 30 min | >1.995 mg/l | activated sludge, domestic | DIN EN ISO 8192 | ECHA |

12.2 Persistence and degradability

Biodegradation

Test data are not available for the complete mixture.

Degradability of components

| Name of substance | CAS No | Process | Degradation rate | Time | Method | Source |
|-------------------|----------|------------------|------------------|------|----------------------|--------|
| propan-2-ol | 67-63-0 | oxygen depletion | 53 % | 5 d | EU method C.5 | ECHA |
| ethylene glycol | 107-21-1 | DOC removal | 90 – 100 % | 10 d | OECD Guideline 301 A | ECHA |
| ethylene glycol | 107-21-1 | oxygen depletion | ≥83 % | 14 d | OECD Guideline 301 C | ECHA |

Persistence

No data available.

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

12.3 Bioaccumulative potential

Bioaccumulative potential of components

| Name of substance | CAS No | BCF | Log KOW |
|-------------------|----------|-----|--------------|
| propan-2-ol | 67-63-0 | - | 0,05 (20 °C) |
| ethylene glycol | 107-21-1 | - | -1,36 |

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0,1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

Data are not available.

Remarks

Wassergefährdungsklasse, WGK (water hazard class): 1.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

This material and its container must be disposed of as hazardous waste.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Completely emptied packages can be recycled.

Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN UN1987

IMDG-Code UN1987

ICAO-TI UN1987

14.2 UN proper shipping name


ADR/RID/ADN ALCOHOLS, N.O.S.

IMDG-Code ALCOHOLS, N.O.S.

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

| | | |
|------|---|--|
| | ICAO-TI | Alcohols, n.o.s. |
| | Technical name (hazardous ingredients) | isopropanol |
| 14.3 | Transport hazard class(es) | |
| | ADR/RID/ADN | 3 |
| | IMDG-Code | 3 |
| | ICAO-TI | 3 |
| 14.4 | Packing group | |
| | ADR/RID/ADN | III |
| | IMDG-Code | III |
| | ICAO-TI | III |
| 14.5 | Environmental hazards | - |
| 14.6 | Special precautions for user | - |
| 14.7 | Maritime transport in bulk according to IMO - instruments | |
| 14.8 | <u>Information for each of the UN Model Regulations</u> | |
| | Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) | |
| | Additional information | |
| | Particulars in the transport document | UN1987, ALCOHOLS, N.O.S., (isopropanol), 3, III, (D/E) |
| | Classification code | F1 |
| | Danger label(s) | 3 |
| |  | |
| | Special provisions (SP) | 274, 601 |
| | Excepted quantities (EQ) | E1 |
| | Limited quantities (LQ) | 5 L |
| | Transport category (TC) | 3 |
| | Tunnel restriction code (TRC) | D/E |
| | Hazard identification No | 30 |

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (ADN) Additional information

Number of cones/blue lights 0

International Maritime Dangerous Goods Code (IMDG) Additional information

Marine pollutant -

Danger label(s) 3



Special provisions (SP) 223, 274

Excepted quantities (EQ) E1

Limited quantities (LQ) 5 L

EmS F-E, S-D

Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) Additional information

Danger label(s) 3



Special provisions (SP) A3, A180

Excepted quantities (EQ) E1

Limited quantities (LQ) 10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

| Name | Name acc. to inventory | CAS No | Restriction |
|-------------------------------|--|--------|-------------|
| Maschinenfrostschutz -15 Grad | this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC | - | R3 |
| propan-2-ol | flammable / pyrophoric | - | R40 |
| propan-2-ol | substances in tattoo inks and permanent make-up | - | R75 |

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

Legend

- R3
1. Shall not be used in:
 - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 - tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
 2. Articles not complying with paragraph 1 shall not be placed on the market.
 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
 - can be used as fuel in decorative oil lamps for supply to the general public, and
 - present an aspiration hazard and are labelled with H304.
 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
 5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
 - (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";
 - (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';
 - (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.;
- R40
1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:
 - metallic glitter intended mainly for decoration,
 - artificial snow and frost,
 - 'whoopie' cushions,
 - silly string aerosols,
 - imitation excrement,
 - horns for parties,
 - decorative flakes and foams,
 - artificial cobwebs,
 - stink bombs.
 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:
'For professional users only'.
 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
- R75
1. Shall not be placed on the market in mixtures for use for tattooing purposes, and mixtures containing any such substances shall not be used for tattooing purposes, after 4 January 2022 if the substance or substances in question is or are present in the following circumstances:
 - (a) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;
 - (b) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as reproductive toxicant category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;
 - (c) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin sensitiser category 1, 1A or 1B, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;
 - (d) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2, or as serious eye damage category 1 or eye irritant category

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

Legend

- 2, the substance is present in the mixture in a concentration equal to or greater than:
- (i) 0,1 % by weight, if the substance is used solely as a pH regulator;
 - (ii) 0,01 % by weight, in all other cases;
 - (e) in the case of a substance listed in Annex II to Regulation (EC) No 1223/2009 (*1), the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;
 - (f) in the case of a substance for which a condition of one or more of the following kinds is specified in column g (Product type, Body parts) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight:
 - (i) "Rinse-off products";
 - (ii) "Not to be used in products applied on mucous membranes";
 - (iii) "Not to be used in eye products";
 - (g) in the case of a substance for which a condition is specified in column h (Maximum concentration in ready for use preparation) or column i (Other) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration, or in some other way, that does not accord with the condition specified in that column;
 - (h) in the case of a substance listed in Appendix 13 to this Annex, the substance is present in the mixture in a concentration equal to or greater than the concentration limit specified for that substance in that Appendix.
2. For the purposes of this entry use of a mixture "for tattooing purposes" means injection or introduction of the mixture into a person's skin, mucous membrane or eyeball, by any process or procedure (including procedures commonly referred to as permanent make-up, cosmetic tattooing, micro-blading and micro-pigmentation), with the aim of making a mark or design on his or her body.
3. If a substance not listed in Appendix 13 falls within more than one of points (a) to (g) of paragraph 1, the strictest concentration limit laid down in the points in question shall apply to that substance. If a substance listed in Appendix 13 also falls within one or more of points (a) to (g) of paragraph 1, the concentration limit laid down in point (h) of paragraph 1 shall apply to that substance.
4. By way of derogation, paragraph 1 shall not apply to the following substances until 4 January 2023:
- (a) Pigment Blue 15:3 (CI 74160, EC No 205-685-1, CAS No 147-14-8);
 - (b) Pigment Green 7 (CI 74260, EC No 215-524-7, CAS No 1328-53-6).
5. If Part 3 of Annex VI to Regulation (EC) No 1272/2008 is amended after 4 January 2021 to classify or re-classify a substance such that the substance then becomes caught by point (a), (b), (c) or (d) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the date of application of that new or revised classification is after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect on the date of application of that new or revised classification.
6. If Annex II or Annex IV to Regulation (EC) No 1223/2009 is amended after 4 January 2021 to list or change the listing of a substance such that the substance then becomes caught by point (e), (f) or (g) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the amendment takes effect after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect from the date falling 18 months after entry into force of the act by which that amendment was made.
7. Suppliers placing a mixture on the market for use for tattooing purposes shall ensure that, after 4 January 2022, the mixture is marked with the following information:
- (a) the statement "Mixture for use in tattoos or permanent make-up";
 - (b) a reference number to uniquely identify the batch;
 - (c) the list of ingredients in accordance with the nomenclature established in the glossary of common ingredient names pursuant to Article 33 of Regulation (EC) No 1223/2009, or in the absence of a common ingredient name, the IUPAC name. In the absence of a common ingredient name or IUPAC name, the CAS and EC number. Ingredients shall be listed in descending order by weight or volume of the ingredients at the time of formulation. "Ingredient" means any substance added during the process of formulation and present in the mixture for use for tattooing purposes. Impurities shall not be regarded as ingredients. If the name of a substance, used as ingredient within the meaning of this entry, is already required to be stated on the label in accordance with Regulation (EC) No 1272/2008, that ingredient does not need to be marked in accordance with this Regulation;
 - (d) the additional statement "pH regulator" for substances falling under point (d)(i) of paragraph 1;
 - (e) the statement "Contains nickel. Can cause allergic reactions." if the mixture contains nickel below the concentration limit specified in Appendix 13;
 - (f) the statement "Contains chromium (VI). Can cause allergic reactions." if the mixture contains chromium (VI)

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

Legend

below the concentration limit specified in Appendix 13;

(g) safety instructions for use insofar as they are not already required to be stated on the label by Regulation (EC) No 1272/2008.

The information shall be clearly visible, easily legible and marked in a way that is indelible.

The information shall be written in the official language(s) of the Member State(s) where the mixture is placed on the market, unless the Member State(s) concerned provide(s) otherwise.

Where necessary because of the size of the package, the information listed in the first subparagraph, except for point (a), shall be included instead in the instructions for use.

Before using a mixture for tattooing purposes, the person using the mixture shall provide the person undergoing the procedure with the information marked on the package or included in the instructions for use pursuant to this paragraph.

8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for tattooing purposes.

9. This entry does not apply to substances that are gases at temperature of 20 °C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 °C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

None of the ingredients are listed.

Seveso Directive

| 2012/18/EU (Seveso III) | | | | |
|-------------------------|---------------------------------------|---|--------|-------|
| No | Dangerous substance/hazard categories | Qualifying quantity (tonnes) for the application of lower and upper-tier requirements | | Notes |
| P5c | flammable liquids (cat. 2, 3) | 5.000 | 50.000 | 51) |

Notation

51) flammable liquids, categories 2 or 3 not covered by P5a and P5b

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

None of the ingredients are listed.

Regulation on the marketing and use of explosives precursors

None of the ingredients are listed.

Regulation on drug precursors

None of the ingredients are listed.

Regulation on substances that deplete the ozone layer (ODS)

None of the ingredients are listed.

Regulation concerning the export and import of hazardous chemicals (PIC)

None of the ingredients are listed.

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

National regulations (Germany)

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK 1
(water hazard class) - classification acc. to annex 1 (AwSV)

Technical instructions on air quality control (Germany)

| Number | Group of substances | Class | Conc. | Mass flow | Mass concentration | Notation |
|--------|---------------------|-------|---------------|-----------|----------------------|----------|
| 5.2.5 | organic substances | - | 10 – < 25 wt% | 0,5 kg/h | 50 mg/m ³ | 3) |

Notation

- 3) a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m³, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

Storage of hazardous substances in non-stationary containers (TRGS 510) (Germany)

Storage class (LGK) 3
(flammable or desensitizing explosive liquids)

Chemikalien-Verbotsverordnung (Chemicals Prohibition Ordinance) - ChemVerbotsV

none of the ingredients are listed

Other information

Observe employment restrictions for young people according to § 22 ArbSchG.
Observe occupational restrictions for mothers acc. to §§ 11 and 12 MuSchG!

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations |
|------------|---|
| 2000/39/EC | Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC |
| Acute Tox. | Acute toxicity |
| ADN | Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) |
| ADR | Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road) |

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

| Abbr. | Descriptions of used abbreviations |
|-------------|---|
| ADR/RID/ADN | Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN) |
| AGW | Workplace exposure limit |
| ATE | Acute Toxicity Estimate |
| BCF | Bioconcentration factor |
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) |
| CLP | Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures |
| CMR | Carcinogenic, Mutagenic or toxic for Reproduction |
| DFG | Deutsche Forschungsgemeinschaft MAK-und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim |
| DGR | Dangerous Goods Regulations (see IATA/DGR) |
| DNEL | Derived No-Effect Level |
| EC50 | Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval |
| EC No | The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union) |
| ED | Endocrine disruptor |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| ELINCS | European List of Notified Chemical Substances |
| EmS | Emergency Schedule |
| Eye Dam. | Seriously damaging to the eye |
| Eye Irrit. | Irritant to the eye |
| Flam. Liq. | Flammable liquid |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations |
| IATA | International Air Transport Association |
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) |
| ICAO | International Civil Aviation Organization |
| ICAO-TI | Technical instructions for the safe transport of dangerous goods by air |
| IMDG | International Maritime Dangerous Goods Code |
| IMDG-Code | International Maritime Dangerous Goods Code |
| index No | The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 |
| IOELV | Indicative occupational exposure limit value |
| LC50 | Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval |

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

| Abbr. | Descriptions of used abbreviations |
|----------|---|
| LD50 | Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval |
| LGK | Lagerklasse (storage class according to TRGS 510, Germany) |
| log KOW | n-Octanol/water |
| NLP | No-Longer Polymer |
| NOEC | No Observed Effect Concentration |
| NOELR | No Observed Effect Loading Rate |
| PBT | Persistent, Bioaccumulative and Toxic |
| ppm | Parts per million |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals |
| RID | Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail) |
| STEL | Short-term exposure limit |
| STOT RE | Specific target organ toxicity - repeated exposure |
| STOT SE | Specific target organ toxicity - single exposure |
| SVHC | Substance of Very High Concern |
| TRGS | Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany) |
| TRGS 900 | Arbeitsplatzgrenzwerte (TRGS 900) |
| TRGS 903 | Biologische Grenzwerte (TRGS 903) |
| TWA | Time-weighted average |
| vPvB | Very Persistent and very Bioaccumulative |

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN).

International Maritime Dangerous Goods Code (IMDG).

Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties.

Health hazards.

Environmental hazards.

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

OPN-Special Coolant for the Welding Technology with frost protection to -10°C

Version number: 9.0

Revision: 02.09.2024

List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text |
|------|--|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

Disclaimer

This information is based upon the present state of our knowledge.

This SDS has been compiled and is solely intended for this product.