

Printing date 02.03.2022 Version number 20 (replaces version 19) Revision: 02.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

·Trade name: OPN-Spray Grease white

·Article number: 61470

Unique formula identifier (UFI): YG7G-C5WC-Y00J-HKJD

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Lubricant

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

OPN-CHEMIE GmbH

In der Au 14

57290 Neunkirchen

www.opn-chemie.de

· Further information obtainable from:

Barbara Angelika Gros-Petri

E-Mail (competent person) baerbel.petri@opn-chemie.de

· 1.4 Emergency telephone number:

Emergency information service Vergiftungs-Informations-Zentrale Freiburg +49 (0) 761 / 1 92 40

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1



environment

Toxic to aquatic life with long lasting effects. Aquatic Chronic 2 H411



Skin Irrit. 2	H315	Causes skin irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

(Contd. on page 2)

Printing date 02.03.2022 Version number 20 (replaces version 19) Revision: 02.03.2022

Trade name: OPN-Spray Grease white

(Contd. of page 1)

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing vapours or spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P391 Collect spillage.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
- P501 Dispose of contents/container to hazardous or special waste collection point.

· Additional information:

EUH208 Contains Polysulfide, Di-tert-dodecyl. May produce an allergic reaction.

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
EC number: 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	20-<25%		
EC number: 927-510-4 Reg.nr.: 01-2119475515-33-xxxx	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	20-<25%		
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<20%		
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane, pure Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%		
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	2.5-<5%		
CAS: 68425-15-0 EINECS: 270-335-7	Polysulfide, Di-tert-dodecyl Skin Sens. 1B, H317; Aquatic Chronic 4, H413	0.1-<1%		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

Printing date 02.03.2022 Version number 20 (replaces version 19) Revision: 02.03.2022

Trade name: OPN-Spray Grease white

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty

Headache

Dizziness

Dizziness

Coughing

Nausea

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

Later observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Fire-extinguishing powder

Carbon dioxide

Use fire extinguishing methods suitable to surrounding conditions.

Foam

\cdot 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

• 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

Printing date 02.03.2022 Version number 20 (replaces version 19) Revision: 02.03.2022

Trade name: OPN-Spray Grease white

(Contd. of page 3)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.2 Exposure controls

· Ingredients with limit values that require monitoring at the workplace:

CAS: 106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

- · Recommended filter device for short term use: Filter AX
- · Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.45 mm

(Contd. on page 5)

Printing date 02.03.2022 Version number 20 (replaces version 19) Revision: 02.03.2022

Trade name: OPN-Spray Grease white

(Contd. of page 4)

· Penetration time of glove material

≥240 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Not required.
- · **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour:
Petrol-like
Odour threshold:
Melting point/freezing point:
Undetermined.

· Boiling point or initial boiling point and boiling

range < 0 °C

· Flammability Not applicable.

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined.

• Flash point: Not applicable, as aerosol.

• Ignition temperature: >200 °C
 • Decomposition temperature: Not determined.
 • pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

 $\cdot \ Solubility$

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure:
 Not determined.
 Not determined.

· Density and/or relative density

Density at 20 °C: 0.70192 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and

environment, and on safety.

Auto-ignition temperature: Not determined.
 Explosive properties: Not determined.

· Solvent separation test:

• Organic solvents: 70.1 %
• VOC (EC) 492.4 g/1
• Solids content: 0.0 %

· Change in condition

• Evaporation rate Not applicable.

· Information with regard to physical hazard classes

Explosives VoidFlammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

(Contd. on page 6)

Printing date 02.03.2022 Version number 20 (replaces version 19) Revision: 02.03.2022

Trade name: OPN-Spray Grease white

		(Contd. of page 5)
· Oxidising gases	Void	
· Gases under pressure	Void	
· Flammable liquids	Void	
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Aldehyde

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

LD/LC50 values relevant for classification:			
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane			
LD50	>5,000 mg/kg (rat) (OECD Prüfrichtlinie 401)		
LD50	>2,000 mg/kg (rat) (OECD Prüfrichtlinie 402)		
LC50/4 h	>20 mg/l (rat) (OECD Prüfrichtlinie 403)		
Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes			
LD50	>5,840 mg/kg (rat)		
LD50	>2,920 mg/kg (rat)		
LC50/4 h	>25.2 mg/l (rat)		
CAS: 74-98-6 propane			
LC50/4 h	>20 mg/l (rat)		
CAS: 106-97-8 butane, pure			
LC50/4 h	658 mg/l (rat)		
CAS: 75-28-5 isobutane			
LC50/4 h	658 mg/l (rat)		
	LD50 LD50 LC50/4 h bons, C7, 1 LD50 LD50 LC50/4 h 8-6 propa LC50/4 h 97-8 buta LC50/4 h 8-5 isobut		

- · Skin corrosion/irritation Causes skin irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · Aspiration hazard May be fatal if swallowed and enters airways.

(Contd. on page 7)

Printing date 02.03.2022 Version number 20 (replaces version 19) Revision: 02.03.2022

Trade name: OPN-Spray Grease white

(Contd. of page 6)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- \cdot 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1	UN	number	or ID	number
17.1	\mathbf{v}_{11}	Humber	\mathbf{u}	Humber

· ADR/RID/ADN, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR/RID/ADN UN1950 AEROSOLS

· IMDG AEROSOLS, MARINE POLLUTANT

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- · ADR/RID/ADN



· Class 2 5F Gases.

(Contd. on page 8)

Printing date 02.03.2022 Version number 20 (replaces version 19) Revision: 02.03.2022

Trade name: OPN-Spray Grease white

	(Contd. of page 7)
· Label	2.1
· IMDG	
· Class	2.1 Gases.
· Label	2.1
· IATA	
· Class	2.1 Gases.
· Class · Label	2.1 Gases. 2.1
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	Product contains environmentally hazardous substances: Solvent Naphta Yes
Special marking (ADR/RID/ADN):	Symbol (fish and tree) Symbol (fish and tree)
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Code Segregation Code 	Warning: Gases. F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk according to IM instruments	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	2 D
	(Contd. on page 9)

Printing date 02.03.2022 Version number 20 (replaces version 19) Revision: 02.03.2022

Trade name: OPN-Spray Grease white

· IMDG
· Limited quantities (LQ)
· Excepted quantities (EQ)

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Skin Sens. 1B: Skin sensitisation - Category 1B

(Contd. on page 10)

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Version number 20 (replaces version 19) Printing date 02.03.2022 Revision: 02.03.2022

Trade name: OPN-Spray Grease white

(Contd. of page 9)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

* Data compared to the previous version altered.