



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

OPN-Aluminium Spray - MIRROR FINISH -

Version number: 5.0
Revision: 2022-01-01

Date of compilation: 2015-11-19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1	Product identifier Trade name	OPN-Aluminium Spray - MIRROR FINISH -
	Unique formula identifier (UFI)	QQGM-T5UQ-N00P-69XR
	Other means of identification	
	Article number	63010
	Tariff No.	32081010
1.2	Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses	Industrial use Professional use Consumer use (private households) 1 pack performance coating
	Sector of use	Aluminium spray
	Uses advised against	Do not use for products which come into contact with foodstuffs
1.3	Details of the supplier of the safety data sheet OPN-CHEMIE GmbH In der Au 14 57290 Neunkirchen www.opn-chemie.de Competent person responsible for the safety data sheet e-mail (competent person)	Barbara Angelika Gros-Petri baerbel.petri@opn-chemie.de
1.4	Emergency telephone number Emergency information service	Vergiftungs-Informations-Zentrale Freiburg +49(0) 761 / 1 92 40

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Hazard class and category	Hazard statement
2.3	Aerosols	Aerosol 1	H222,H229
3.3	Serious eye damage/eye irritation	Eye Irrit. 2	H319
3.8R	Specific target organ toxicity - single exposure (respiratory tract irritation)	STOT SE 3	H335
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	STOT SE 3	H336
4.1C	Hazardous to the aquatic environment - chronic hazard	Aquatic Chronic 3	H412

Code	Supplemental hazard information
EUH066	Repeated exposure may cause skin dryness or cracking

Remarks

For full text of abbreviations: see SECTION 16
The most important adverse physicochemical, human health and environmental effects
Spillage and fire water can cause pollution of watercourses.

- 2.2 Label elements
Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word Danger

Pictograms

GHS02, GHS07



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

OPN-Aluminium Spray - MIRROR FINISH -

Version number: 5.0
Revision: 2022-01-01

Date of compilation: 2015-11-19

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P271 Use only outdoors or in a well-ventilated area.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P501 Dispose of contents / container in accordance with national regulations of the disposal.

Additional labelling requirements

EUH066 Repeated exposure may cause skin dryness or cracking.
Buildup of explosive mixtures possible without sufficient ventilation.

Hazardous ingredients for labelling

Ethyl acetate
Hydrocarbons, C9, aromatics

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients







3.1 Substances

Not relevant (mixture).

3.2 Mixtures

Description of the mixture

Mixture of substances listed below with nonhazardous additions

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Butane	CAS No 106-97-8 EC No 203-448-7 Index No 601-004-00-0 REACH Reg. No 01-2119474691-32- xxxx	25 – < 50	Flam. Gas 1 / H220 Press. Gas L / H280	 
Ethyl acetate	CAS No 141-78-6 EC No 205-500-4 REACH Reg. No 01-2119475103-46- xxxx	10 – < 25	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	 
Propane	CAS No 74-98-6 EC No 200-827-9 REACH Reg. No 01-2119486944-21- xxxx	10 – < 25	Flam. Gas 1 / H220 Press. Gas L / H280	 




Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

OPN-Aluminium Spray - MIRROR FINISH -

Version number: 5.0
Revision: 2022-01-01

Date of compilation: 2015-11-19

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Hydrocarbons, C9, aromatics	EC No 918-668-5 REACH Reg. No 01-2119455851-35- xxxx	5 – < 10	Flam. Liq. 3 / H226 STOT SE 3 / H335 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	
Aluminium	CAS No 7429-90-5 EC No 231-072-3 Index No 013-001-00-1 REACH Reg. No 01-2119529243-45- xxxx	1 – < 5	Flam. Sol. 1 / H228	
Isobutane	CAS No 75-28-5 EC No 200-857-2 REACH Reg. No 01-2119485395-27- xxxx	1 – < 5	Flam. Gas 1 / H220 Press. Gas L / H280	

- 3.3 Remarks
For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

OPN-Aluminium Spray - MIRROR FINISH -

Version number: 5.0
Revision: 2022-01-01

Date of compilation: 2015-11-19

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
Suitable extinguishing media
Water spray. BC-powder.
Unsuitable extinguishing media
Water jet.
- 5.2 Special hazards arising from the substance or mixture
In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.
Hazardous combustion products
Carbon monoxide (CO). Carbon dioxide (CO₂).
- 5.3 Advice for firefighters
In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
For non-emergency personnel
Remove persons to safety.
For emergency responders
Wear breathing apparatus if exposed to vapours/dust/spray/gases.
- 6.2 Environmental precautions
Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.
- 6.3 Methods and material for containment and cleaning up
Advice on how to contain a spill
Covering of drains.
Other information relating to spills and releases
Place in appropriate containers for disposal. Ventilate affected area.
- 6.4 Reference to other sections
Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Recommendations
Measures to prevent fire as well as aerosol and dust generation
Use local and general ventilation. Use only in well-ventilated areas.
Advice on general occupational hygiene
Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.
- 7.2 Conditions for safe storage, including any incompatibilities
Managing of associated risks
Storage class (LGK)
2 B
- Flammability hazards
- Do not spray on an open flame or other ignition source. Protect from sunlight.
Consideration of other advice
- Packaging compatibilities
- Only packagings which are approved (e.g. acc. to ADR) may be used.
- 7.3 Specific end use(s)
No further relevant information available.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

OPN-Aluminium Spray - MIRROR FINISH -

Version number: 5.0
Revision: 2022-01-01

Date of compilation: 2015-11-19

SECTION 8: Exposure controls/personal protection

8.1 Control parameters National limit values

This information is not available.

Relevant DNELs/DMELs/PNECs and other threshold levels

Relevant DNELs of components of the mixture

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Hydrocarbons, C9, aromatics		DNEL	150 mg/m ³	Human, inhalatory	Worker (industry)	Chronic - systemic effects
Hydrocarbons, C9, aromatics		DNEL	25 mg/kg bw/day	Human, dermal	Worker (industry)	Chronic - systemic effects
Aluminium	7429-90-5	DNEL	3.72 mg/m ³	Human, inhalatory	Worker (industry)	Chronic - local effects

Relevant PNECs of components of the mixture

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Ethyl acetate	141-78-6	PNEC	650 mg/l	Microorganisms	Sewage treatment plant (STP)	Short-term (single instance)
Ethyl acetate	141-78-6	PNEC	1.65 mg/l	Aquatic organisms	Water	Intermittent release
Aluminium	7429-90-5	PNEC	74.9 µg/l	Aquatic organisms	Freshwater	Short-term (single instance)
Aluminium	7429-90-5	PNEC	20 mg/l	Microorganisms	Sewage treatment plant (STP)	Short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Do not spray in eyes. If required use tight-fitting goggles.

Skin protection

Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374.

Type of material

IR: isobutene-isoprene (butyl) rubber.

Material thickness

> 0,7 mm

Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

Operate if possible out of doors or in a well-ventilated place. In case of inadequate ventilation wear respiratory protection. Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

OPN-Aluminium Spray - MIRROR FINISH -

Version number: 5.0
Revision: 2022-01-01

Date of compilation: 2015-11-19

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	Aerosol (Spray aerosol)
Colour	Silver
Odour	Solvent like
Other safety parameters	
Initial boiling point and boiling range	Not applicable, as aerosol.*
Flash point	Not applicable, as aerosol.*
Flammability (solid, gas)	Flammable aerosol in accordance with GHS criteria
Explosive limits	
• Lower explosion limit (LEL)	2.2 vol%
• Upper explosion limit (UEL)	15 vol%
Vapour pressure	3.8 bar at 20 °C
	6.8 bar at 50 °C
Density	0.67 g/ml at 20 °C
Water solubility	Insoluble
Viscosity	Not relevant (Aerosol)

9.2 Other information

* The finished mixture in an aerosol container is formed after addition of propellant. Several details are not measurable in an hermetic closed, pressurized container.

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

Physical stresses which might result in a hazardous situation and have to be avoided

High temperatures.

10.5 Incompatible materials

Oxidisers.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Aluminium	7429-90-5	Inhalation: dust/mist	0.888 mg/l/4h

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

OPN-Aluminium Spray - MIRROR FINISH -

Version number: 5.0
Revision: 2022-01-01

Date of compilation: 2015-11-19

Skin corrosion/irritation
Shall not be classified as corrosive/irritant to skin.
Serious eye damage/eye irritation
Causes serious eye irritation.
Respiratory or skin sensitisation
Shall not be classified as a respiratory or skin sensitiser.
Germ cell mutagenicity
Shall not be classified as germ cell mutagenic.
Carcinogenicity
Shall not be classified as carcinogenic.
Reproductive toxicity
Shall not be classified as a reproductive toxicant.
• Specific target organ toxicity - single exposure
May cause respiratory irritation. May cause drowsiness or dizziness.
• Specific target organ toxicity - repeated exposure
Shall not be classified as a specific target organ toxicant (repeated exposure).
Aspiration hazard
Shall not be classified as presenting an aspiration hazard.
Other information
Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.
Ordinance on systems for handling water-polluting substances (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK (Germany) 2, obviously hazardous to water

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Ethyl acetate	141-78-6	EC50	2,306 mg/l	Aquatic invertebrates	24 h
Hydrocarbons, C9, aromatics		EL50	4.1 mg/l	Aquatic invertebrates	24 h
Hydrocarbons, C9, aromatics		EC50	>99 mg/l	Microorganisms	10 min

12.2 Persistence and degradability

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
Ethyl acetate	141-78-6	Oxygen depletion	62 %	5 d		
Hydrocarbons, C9, aromatics		Oxygen depletion	30.9 %	2 d		ECHA

12.3 Bioaccumulative potential

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

OPN-Aluminium Spray - MIRROR FINISH -

Version number: 5.0
Revision: 2022-01-01

Date of compilation: 2015-11-19

Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Butane	106-97-8		1.09 (pH value: 7, 20 °C)	
Ethyl acetate	141-78-6	30	0.68 (pH value: 7, 25 °C)	
Propane	74-98-6		1.09 (pH value: 7, 20 °C)	
Isobutane	75-28-5		1.09 (pH value: 7, 20 °C)	

- 12.4 Mobility in soil
Data are not available.
- 12.5 Results of PBT and vPvB assessment
Data are not available.
- 12.6 Other adverse effects
Endocrine disrupting potential
None of the ingredients are listed.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
Sewage disposal-relevant information
Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.
Waste treatment of containers/packagings
It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.
Relevant provisions relating to waste
List of wastes
15 01 04 Metallic packaging
15 01 10 Packaging containing residues of or contaminated by dangerous substances
16 05 04 Containing hazardous gases in pressure containers (including halons)
Remarks
Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

- 14.1 UN number 1950
- 14.2 UN proper shipping name AEROSOLS
- 14.3 Transport hazard class(es)
Class 2 (Gases) (Aerosol)
Subsidiary risk(s) 2.1 (Flammable)
- 14.4 Packing group Not assigned to a packing group
- 14.5 Environmental hazards Non-environmentally hazardous acc. to the dangerous goods regulations
- 14.6 Special precautions for user
Provisions for dangerous goods (ADR) should be complied within the premises.
- 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code
The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

OPN-Aluminium Spray - MIRROR FINISH -

Version number: 5.0
Revision: 2022-01-01

Date of compilation: 2015-11-19

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

UN number 1950
Proper shipping name AEROSOLS
Class 2
Classification code 5F
Danger label(s) 2.1



Special provisions (SP) 190, 327, 344, 625
Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
Transport category (TC) 2
Tunnel restriction code (TRC) D
International Maritime Dangerous Goods Code (IMDG)
UN number 1950
Proper shipping name AEROSOLS
Class 2.1
Marine pollutant -
Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 959
Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
EmS F-D, S-U
Stowage category -
International Civil Aviation Organization (ICAO-IATA/DGR)
UN number 1950
Proper shipping name Aerosols, flammable
Class 2.1
Danger label(s) 2.1



Special provisions (SP) A145, A167
Excepted quantities (EQ) E0
Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Relevant provisions of the European Union (EU)
- Restrictions according to REACH, Annex XVII
- none of the ingredients are listed
- List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list
- none of the ingredients are listed
- Directive 75/324/EEC relating to aerosol dispensers
- Classification of the gas/aerosol Extremely flammable
- Labelling Keep out of reach of children. Pressurized container: may burst if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
- Additional information -
- Deco-Paint Directive (2004/42/EC)
- VOC content 90.11 %
603.8 g/l
The maximum content of VOC of the product in a ready to use condition

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

OPN-Aluminium Spray - MIRROR FINISH -

Version number: 5.0
Revision: 2022-01-01

Date of compilation: 2015-11-19

Maximum VOC content limit				
Product category	Product subcategory	Coating	Type	VOC g/l
Vehicle refinishing products	Special finishes	All types		840

Directive on industrial emissions (VOCs, 2010/75/EU)

VOC content 90.11 %

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II

none of the ingredients are listed

Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Water Framework Directive (WFD)

none of the ingredients are listed

National regulations (Germany)

Ordinance on systems for handling water-polluting substances (Ordinance on facilities for handling substances hazardous to water)(AwSV)

Water hazard class 2 (obviously hazardous to water)

Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concentration	Notation
5.2.5	Organic substances		≥ 25 wt%	0.5 kg/h	50 mg/m ³	3)

Notation

3) A total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m³, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

Storage of hazardous substances in non-stationary containers (TRGS 510) (Germany)

Storage class (LGK) 2 B (Aerosol dispensers and lighters)

National inventories

Country	Inventory	Status
EU	REACH Reg.	Not all ingredients are listed

Legend

REACH Reg. REACH registered substances

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways).
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard.
Asp. Tox.	Aspiration hazard.
ATE	Acute Toxicity Estimate.
BCF	Bioconcentration factor.
BOD	Biochemical Oxygen Demand.
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances).
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
COD	Chemical oxygen demand.
DGR	Dangerous Goods Regulations (see IATA/DGR).
DMEL	Derived Minimal Effect Level.
DNEL	Derived No-Effect Level.
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval.
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union).
EINECS	European Inventory of Existing Commercial Chemical Substances.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

OPN-Aluminium Spray - MIRROR FINISH -

Version number: 5.0
Revision: 2022-01-01

Date of compilation: 2015-11-19

EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms.
ELINCS	European List of Notified Chemical Substances.
EmS	Emergency Schedule.
Eye Dam.	Seriously damaging to the eye.
Eye Irrit.	Irritant to the eye.
Flam. Gas	Flammable gas.
Flam. Liq.	Flammable liquid.
Flam. Sol.	Flammable solid.
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations.
IATA	International Air Transport Association.
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA).
ICAO	International Civil Aviation Organization.
IMDG	International Maritime Dangerous Goods Code.
Index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008.
LGK	Lagerklasse (storage class according to TRGS 510, Germany).
Log KOW	n-Octanol/water.
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant").
NLP	No-Longer Polymer.
PBT	Persistent, Bioaccumulative and Toxic.
PNEC	Predicted No-Effect Concentration.
Press. Gas	Gas under pressure.
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals.
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail).
STOT SE	Specific target organ toxicity - single exposure.
SVHC	Substance of Very High Concern.
TRGS	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany).
VOC	Volatile Organic Compounds.
VPvB	Very Persistent and very Bioaccumulative.

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN).

International Maritime Dangerous Goods Code (IMDG).

Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture.

Health hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.